

ASHRAE 110-2016: SEFA 1-2010

Flow Containment & Instrumentation

## CERTIFICATE OF TYPE TESTING IN ACCORDANCE WITH ASHRAE 110-2016

CERTIFICATE & REPORT NO: INV/ASHRAE110/901 DATE: 7th June 2019

**Fume Hood Manufacturer:** 

Esco Micro Pte Ltd 21 Changi South Street 1 Singapore 486 777



**Fume Hood Model/Type:** 

PPH-6UDPVW-8
1.8m wide bench-type

**External Dimensions:** 

 Height =
 1500mm

 Width =
 1800mm

 Depth =
 900mm (max)

 Internal Dimensions:

Height = 1200mm (max) Width = 1580mm (max) Depth = 665mm (max)

Test Opening: Width: 1580mm Height: 440mm

**Fume Hood Flow:** 

**Face velocity: 100ft/min** (0.51m/s) **Flow rate: 855cfm** (1455m3/hr)

**Fume Hood Containment:** 

At all test positions: <0.010ppm Test opening scans: <0.050ppm Sash movement effect: <0.010ppm

This is to certify that the fume hood described above has been typetested in accordance with ASHRAE 110-2016, as required by SEFA 1-2010, and resulted in performance characteristics given in the corresponding test report.

Tested and Certified by: Dr A F Bicen

H.F. Dicen

**Invent UK Ltd, 85 Southdown Road, Harpenden, Herts AL5 1PR** T: +44 (0) 1582 461666 F: +44 (0) 1582 460077 E: info@invent-uk.com